



# The Gorman-Rupp Company

## 60 Series

Gorman-Rupp 60 Series pumps are standard centrifugal, high pressure, high volume pumps with exceptional efficiencies (up to 85%). Discharge on many models can be placed in any position by turning the pump casing.



### Specifications

Size:	3" (75 mm), 4" (100 mm), 5" (125 mm), 6" (150 mm), 8" (200 mm), 10" (250 mm), 12" (300 mm)
Max Capacity:	6,800 GPM (429 lps)
Max Head:	500' (152 m)
Max Solids:	3" (76 mm)
Max Temperature:	160 F (71 C)
Materials of Construction:	Cast Iron, Cast Steel, Ductile Iron

*Specifications are subject to change. Please contact your Gorman-Rupp Distributor for more details.*



**The Gorman-Rupp Company**  
**Mansfield Division**  
P.O. Box 1217  
Mansfield, Ohio 44901-1217  
Tel: 419-755-1011  
Fax: 419-755-1251  
E-mail:  
grsales@gormanrupp.com

**The Gorman-Rupp International Company**  
P.O. Box 1217  
Mansfield, Ohio 44901-1217  
Tel: 419-755-1011  
Fax: 419-755-1266  
E-mail: intsales@gormanrupp.com

**Gorman-Rupp of Canada, Ltd.**  
70 Burwell Road  
St. Thomas, Ontario N5P 3R7,  
Canada  
Tel: 519-631-2870  
Fax: 519-631-4624  
E-mail:  
grcanada@grcanada.com



[www.GRpumps.com](http://www.GRpumps.com)

©1998-2007 The Gorman-Rupp Company. All Rights Reserved.